

Application No. 10/689,587

**In the claims:**

1. (currently amended) A method comprising:  
winding a first layer of a lignocellulosic material about a mandrel, said lignocellulosic not having been substantially pre-treated with bitumen; and  
bonding a second layer of a lignocellulosic material to said first layer with a bitumen-based adhesive, wherein an active component of said bitumen-based adhesive is bitumen, and wherein ~~at least one of said first and second layers comprises a~~ lignocellulosic material.
2. (cancelled)
3. (original) The method according to claim 1, further comprising forming a spiral-wound tube by winding said first and second layers at an angle less than a right angle to said mandrel.
4. (original) The method according to claim 1, further comprising forming a convolute-wound tube by winding said first and second layers generally perpendicularly to said mandrel.
5. (original) The method according to claim 1, wherein said bitumen-based adhesive comprises at least one of an additive and a filler.
6. (original) The method according to claim 1, wherein said bitumen comprises at least one of asphalt, coal tar, pitch, VR (Vacuum Residue of low vacuum distillation) bitumen, DVR (Deep Vacuum Residue) bitumen, PA (Precipitated Asphalt), and PPA (Propane Precipitated Asphalt), BB (Blown Bitumen).
7. (original) The method according to claim 5, wherein said additive comprises at least one of a natural polymer, synthetic polymer, wax, oil, solvent, surfactant, biocide, fungicide, and fire retarder.
8. (original) The method according to claim 7, wherein said synthetic polymer comprises at least one of polyethylene, polypropylene, polybutylene, SBS (Styrene Butadiene Styrene), BR (Butadiene Rubber), EVA (Ethylene Vinyl Acetate copolymer), PS (polystyrene) and acrylic resin.
9. (original) The method according to claim 5, wherein said filler comprises at least one of limestone, gypsum, kaolin, talc, mica, coal-ash, cotton, natural fiber, pulp and synthetic fiber.
10. (currently amended) A method comprising:  
forming a corrugated board by bonding a corrugated sheet to at least one outer sheet with a bitumen-based adhesive, wherein an active component of said bitumen-based adhesive is bitumen, and wherein ~~at least one of both~~ said corrugated sheet and said outer

Application No. 10/689,587

sheet comprises a lignocellulosic material that has not been substantially pre-treated with bitumen.

11. (currently amended) An article comprising:

a wound tube formed by winding a first layer of a material about a mandrel, and bonding a second layer of a material to said first layer with a bitumen-based adhesive, wherein an active component of said bitumen-based adhesive is bitumen, and wherein at least one of both said first and second layers comprises a lignocellulosic material that has not been substantially pre-treated with bitumen.

12. (cancelled)

13. (original) The article according to claim 11, wherein said wound tube comprises a spiral-wound tube formed by winding said first and second layers at an angle less than a right angle to said mandrel.

14. (original) The article according to claim 11, wherein said wound tube comprises a convolute-wound tube by winding said first and second layers generally perpendicularly to said mandrel.

15. (original) The article according to claim 11, wherein said bitumen-based adhesive comprises at least one of an additive and a filler.

16. (original) The article according to claim 11, wherein said bitumen comprises at least one of asphalt, coal tar, pitch, VR (Vacuum Residue of low vacuum distillation) bitumen, DVR (Deep Vacuum Residue) bitumen, PA (Precipitated Asphalt), PPA (Propane Precipitated Asphalt), BB (Blown Bitumen).

17. (original) The article according to claim 15, wherein said additive comprises at least one of a natural polymer, synthetic polymer, wax, oil, solvent, surfactant, biocide, fungicide, and fire retarder.

18. (original) The article according to claim 17, wherein said synthetic polymer comprises at least one of polyethylene, polypropylene, polybutylene, SBS (Styrene Butadiene Styrene), BR (Butadiene Rubber), EVA (Ethylene Vinyl Acetate copolymer), PS (polystyrene) and acrylic resin.

19. (original) The article according to claim 15, wherein said filler comprises at least one of limestone, gypsum, kaolin, talc, mica, coal-ash, cotton, natural fiber, pulp and synthetic fiber.

20. (currently amended) An article comprising:

a corrugated board formed by bonding a corrugated sheet to at least one outer sheet with a bitumen-based adhesive, wherein an active component of said bitumen-based

Application No. 10/689,587

adhesive is bitumen, and wherein ~~at least one of both~~ said corrugated sheet and said outer sheet comprises a lignocellulosic material that has not been substantially pre-treated with bitumen.